

Type	C10-T1x/ ... V Standard relay for low power application			
Maximum contact load	6 A/250 V AC-1	0,5 A/110 V DC-1		
	6 A/30 V DC-1	0,2 A/220 V DC-1		
Recommended minimum contact load	5 mA/5 V Code 1			
	1 mA/5 V Code 3			

Contacts			
Material	Standard	Code 1	AgNi + 0,2 μ Au
	Optional	Code 3	AgNi + 3 μ Au
Rated current	6 A		
Switch-on current max. (20 ms)	15 A		
Switching voltage max	250 V		
AC load (Fig 1)	1,5 kVA		
DC load	see fig. 2		

Coil	
Coil resistance	see table; tolerance ± 10 %
Pick-up voltage	≤ 0,8 × U _N
Release voltage	≥ 0,1 × U _N
Nominal power	1,1 VA (AC)/0,7 W (DC)

Coil table																															
	<table border="1"> <thead> <tr> <th>VAC</th> <th>Ω</th> <th>mA</th> <th>VDC</th> <th>Ω</th> <th>mA</th> </tr> </thead> <tbody> <tr> <td>24</td> <td>290</td> <td>45</td> <td>12</td> <td>224</td> <td>53</td> </tr> <tr> <td>48</td> <td>1200</td> <td>23</td> <td>24</td> <td>742</td> <td>32</td> </tr> <tr> <td>115</td> <td>7.300</td> <td>9,5</td> <td>48</td> <td>3.500</td> <td>13,7</td> </tr> <tr> <td>230</td> <td>28.800</td> <td>4,7</td> <td>110</td> <td>19.900</td> <td>5,5</td> </tr> </tbody> </table>	VAC	Ω	mA	VDC	Ω	mA	24	290	45	12	224	53	48	1200	23	24	742	32	115	7.300	9,5	48	3.500	13,7	230	28.800	4,7	110	19.900	5,5
VAC	Ω	mA	VDC	Ω	mA																										
24	290	45	12	224	53																										
48	1200	23	24	742	32																										
115	7.300	9,5	48	3.500	13,7																										
230	28.800	4,7	110	19.900	5,5																										

Insulation	Volt rms, 1 min
Contact open	1000 V
Contact/coil	5 kV
Insulation resistance at 500 V	≥ 1 GΩ
Insulation, IEC 61810-1	4 kV/3

Specifications	
Ambient temperature operation/storage	-40 (no ice)...70 °C / -40 ... 80 °C
Pick-up time/bounce time	10 ms/≤ 1 ms
Release time/bounce time	5 ms/≤ 3 ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance at rated load	≥ 100000 switching cycles
Switching frequency at rated load	1200/h
Protection class	IP40
Weight	21 g

Standard types		
VAC 50 Hz/60 Hz: 24, 48, 115 (120), 230 (240)	C10-T11/AC ... V	C10-T13/AC ... V
LED	C10-T11X/AC ... V	C10-T13X/AC ... V
RC suppressor	C10-T11R/AC...V	C10-T13R/AC...V
VDC12, 24, 48, 110	C10-T11/DC ... V	C10-T13/DC ... V
LED	C10-T11X/DC ... V	C10-T13X/DC ... V
Polarity and free wheeling diode	C10-T11FX/DC ... V	C10-T13FX/DC ... V
AC/DC bridge rectifier 24 V, 48 V	C10-T11BX/UC ... V	C10-T13BX/UC ... V

"..." Enter the voltage for full type designation

Accessories	
Socket:	S10, S10-P



Connection diagram




Fig. 1 AC voltage endurance






Fig. 2 DC load limit curve



Dimensions [mm]



Technical approvals, conformities



IEC 61810; EN 60947