

Type	C2-G2x/ ... V Standard relays, DC application 2 open contacts		
-------------	--	--	--

Maximum contact load	10 A/250 V AC-1	1,2 A/110 V DC-1
	10 A/30 V DC-1	0,4 A/220 V DC-1

Contacts

Material	Standard	Code 0	AgNi
Rated current			10 A
Switch-on current max. (20 ms)			30 A
Switching voltage max.			250 V
AC load (Fig 1)			2,5 kVA
DC load			see Fig. 2

Coil

Coil resistance	see table; tolerance $\pm 10\%$
Pick-up voltage	$\leq 0,8 \times U_N$
Release voltage	$\geq 0,1 \times U_N$
Nominal power	2,4 VA (AC)/1,6 W (DC)

Coil table

VAC	Ω	mA	VDC	Ω	mA
24	65	100	24	360	66
48	286	50	48	1K4	34
115	1K7	21	110	7K6	15
230	6K8	10	220	30K3	7,5

Insulation

	Volt rms, 1 min
Contact open	2000 V
Contact/contact	2,5 kV
Contact/coil	2,5 kV
Insulation resistance at 500 V	$\geq 1 \text{ G}\Omega$
Insulation, EN 61810-1	2,5 kV/3

Specifications






Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Pick-up time/bounce time	20 ms/ ≤ 3 ms
Release time/bounce time	8 ms/ ≤ 1 ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance at rated load	≥ 100000 switching cycles
Switching frequency at rated load	≤ 1200 /ops/h
Protection class	IP40
Weight	79 g

Standard types**VAC 50 Hz/60 Hz: 24, 48, 115 (120), 230 (240)****LED****VDC 24, 48, 110, 220****LED****Free wheeling diode****Polarity and free wheeling diode****AC/DC bridge rectifier 24 V, 48 V, 60 V****C2-G20/AC ... V**
C2-G20X/AC ... V**C2-G20/DC ... V**
C2-G20X/DC ... V
C2-G20DX/DC ... V
C2-G20FX/DC ... V**C2-G20BX/UC ... V**

"..." Enter the voltage for full type designation

Accessories

Socket:	S2-B, S2-S, S2-L, S2-P, S2-P0
Optional accessories (blanking plug):	SO-NP, SO-OP
Retaining clip, plastic:	S30-CM

**Connection diagram****Gap:**
1,7 mm**Fig. 1 AC voltage endurance****Fig. 2 DC load limit curve****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947