

**C4-X2x****14-pin, power relay, double-make, faston**

<b>Type</b>	<b>C4-X2x/ ... V</b> Power relays, DC application 2-pole, NO, double make
-------------	---

<b>Maximum contact load</b>	<b>10 A/250 V AC-1</b> <b>7 A/110 V DC-1</b>
	<b>10 A/30 V DC-1</b> <b>1,2 A/220 V DC-1</b>

**Contacts**

Material	Standard	Code 0	AgNi
Rated current			10 A
Switch-on current max. (20 ms)			30 A
Switching voltage max			250 V
AC load (Fig 1)			2,5 kVA
DC load			see Fig. 2

**Coil**

Coil resistance	see table; tolerance $\pm 10\%$
Pick-up voltage	$\leq 0,8 \times U_N$
Release voltage	$\geq 0,1 \times U_N$
Nominal power	2,4 VA (AC)/1,3 W (DC)

**Coil table**

VAC	$\Omega$	mA	VDC	$\Omega$	mA
24	65	100	24	443	54
48	286	50	48	1K8	27
115	1K7	21	110	9K2	12
230	6k8	10	220	36K1	6

**Insulation**

	Volt rms, 1 min
Contact open	2500 V
Contact/contact	2,5 kV
Contact/coil	2,5 kV
Insulation resistance at 500 V	$\geq 1$ G $\Omega$
Insulation, IEC 61810-1	2,5 kV/3

**Specifications**

Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Pick-up time/bounce time	20 ms/ $\leq 3$ ms
Release time/bounce time	8 ms/ $\leq 1$ ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance at rated load	$\geq 100000$ switching cycles
Switching frequency at rated load	$\leq 1200$ /ops/h
Protection class	IP40
Weight	90 g

**Standard types**

VAC 50 Hz/60 Hz: 24, 48, 115, (120), 230, (240)

LED

RC suppressor

VDC 24, 48, 110, 220

LED

Free wheeling diode

Polarity and free wheeling diode

AC/DC bridge rectifier 24 V, 48 V, 60 V

C4-X20/AC ... V

C4-X20X/AC ... V

C4-X20R/AC ... V

C4-X20/DC ... V

C4-X20X/DC ... V

C4-X20DX/DC ... V

C4-X20FX/DC ... V

C4-X20BX/UC ... V

"... " Enter the voltage for full type designation





**Accessories**

Socket:

S4-S, S4-L, S4-P, S4-PO

Optional accessories (blanking plug):

SO-NP, SO-OP

**Connection diagram****Fig. 1 AC voltage endurance****Fig. 2 DC load limit curve****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947