

Type	C5-M1x/ ... V Power relays, DC application 1 pole, NO, magnetic blow out			
Maximum contact load	16 A/400 V AC-1 3,6 A/110 V DC-13	10 A/220 V 2 A/220 V	DC-1 DC-13	

Contacts

Material	Standard	Code 0	AgNi
Rated current			16 A
Switch-on current max. (20 ms)			40 A
Switching voltage max.			400 V
AC load (Fig 1)			4 kVA
DC load			see Fig. 2

Coil

Coil resistance	see table; tolerance $\pm 10\%$
Pick-up voltage	$\leq 0,8 \times U_N$
Release voltage	$\geq 0,1 \times U_N$
Nominal power	2,4 VA (AC)/1,3 W (DC)

Coil table

VAC	Ω	mA	VDC	Ω	mA
24	65	100	12	110	108
48	286	50	24	443	54
115	1K7	21	48	1K7	27
230	6K8	10	110	9K2	12
400	18K8	6	220	34K5	6,2

Insulation

	Volt rms, 1 min
Contact open	4000 V
Contact/contact	4 kV
Contact/coil	4 kV
Insulation resistance at 500 V	$\geq 3 \text{ G}\Omega$
Insulation, IEC 61810-1	4 kV/3

Specifications

Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Pick-up time/bounce time	20 ms/ ≤ 3 ms
Release time/bounce time	10 ms/ ≤ 1 ms
Mechanical life ops	AC: 10 Mill./DC: 20 Mill.
DC voltage endurance	see fig. 2
Switching frequency at rated load	$\leq 1200/\text{h}$
Protection class	IP40
Weight	90 g

Standard types

VAC 50 Hz/60 Hz: 24, 48, 115 (120), 230 (240)

LED

RC suppressor (max 250 V)

VDC 12, 24, 48, 110, 220

LED

Free wheeling diode

Polarity and free wheeling diode

AC/DC bridge rectifier 24 V, 48 V, 60 V

C5-M10/AC ... V

C5-M10X/AC ... V

C5-M10R/AC ... V

C5-M10/DC ... V

C5-M10X/DC ... V

C5-M10DX/DC ... V






C5-M10FX/DC ... V

C5-M10BX/UC ... V

"..." Enter the voltage for full type designation

Accessories

Socket:	S5-S, S5-L, S5-P, S5-P0, S5-M
Optional accessories (blinking plug):	SO-NP, SO-OP

**Connection diagram****Fig. 1 AC voltage endurance****Fig. 2 DC voltage endurance****Dimensions [mm]****Technical approvals, conformities**

IEC 61810; EN 60947