



<b>Type</b>	<b>S7-I/O</b> 2-pole, 2 level Integrated clip and marking label Coil bridge bus bar to connect in A2 Logic wiring
<b>Rated current</b>	<b>10 A</b>
<b>Specifications</b>	
Rated load	10 A / 250 V
Insulation	Test voltage V rms / 1 min
- All terminals/DIN rail	2,5 kV
- Terminal/terminal	2,5 kV
Cross-section of connecting wire	
- Single-wire	4 mm <sup>2</sup> or 2 x 2,5 mm <sup>2</sup>
- Multi-wire	22 - 14 AWG
Max. screw torque	1,2 Nm
Screw dimensions	M3, Pozi, slot
Integrated retaining clip/plastic	for relay series C7
Labelling space	detachable
Connection label	1...8; DIN/EN
Mounting	DIN rail TS35 or mounting plate
Ambient temperature operation/storage	-40 (no ice)...60 °C / -40 ... 80 °C
Weight	38g
<b>Associated, plug-in 8-pin QRC relays</b>	<b>C7-A2x, C7-T, C7-G, C7-X, C7-W, C7-H</b>
<b>Accessories</b>	
Coil bridge bus bar	<b>S7-BB</b>
Retaining clip, plastic	<b>CP-01B</b>



**Connection diagram**



**Dimensions [mm]**



Sockets 4.0

**4**

**Technical approvals, conformities**



EN 60947-1, EN 61810-1